

# FLOS

■ F0406030 Black


## Arrangements Round Small

Designed by Michael Anastassiades, 2018



21W - 1068lm - 2700K

Diffuse light suspended lighting device. Body in extruded, curved NC-machined and black powder-coated aluminium, diffuser in platinum optical silicone. Each component can be connected to the power pack by means of an electrical and mechanical connection system designed for customisable product set-up. Roses available with two powers: lamp with power under 70W and lamp with power under 190W. Class III roses also available for installations with remote power supply: "surface" version for installations on cement, "recessed" version for plasterboard ceilings. The electronics integrated in the rose enables use of dimming systems: push, 1-10, potentiometer, DALI. In the absence of these systems, the light flow can be set with the push system included in the rose. Cable length 2.4m



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

### Main specifications

EAN	8059607014103
Mounting	Suspension
Environment	Indoor dry location
Light source type	LED
LED type	LED Module
Lamp holder	LED Module
Number of heads	1
Power (W)	21
System flux (lm)	1068

### Physical

Colour	Black
Cord length (mm)	2500
Net weight (kg)	0.41
Package height (cm)	5
Package width (cm)	48
Package length (cm)	51
Package volume (m3)	0.01
IP	20
IP external	20

### Download

[Mounting instructions](#) PDF

[Spare Parts](#) PDF

### Photometric Files

[LDT / IES](#) LDT

### Technical Drawings

[2D](#) ZIP

[3D](#) ZIP



<https://professional.flos.com/en/global/product/arrangements-round-small-f0406030/>


F0406030

©2022 Flos - P.IVA 00290820174 - 8/17/2022

[professional.flos.com](https://professional.flos.com) | [info@flos.com](mailto:info@flos.com) 1/3

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order to improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.


## Schematic light drawing



## Ecodesign and Energy

### Labelling

This product contains a light source of energy efficiency class F



Replaceable (LED only)  
light source by a  
professional


## Photometric

Lighting type	Indirect, Direct
Light distribution	Symmetric
CCT (K)	2700

## Electrical

Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	48
Driver	Remote
Dimmable	Yes
Dimming interface	Remote Dimmable (Dimmer Not Included)
Cord length (mm)	2500
Batteries inside	No
Charging min time	No

## Accessories & Power Supply



REQUIRED

F0415030


Arrangements Big Rose



REQUIRED

F0418030

Arrangements Recessed Rose



REQUIRED

F0416030

Arrangements Small Rose