

FLOS

■ F0409030 Black


Arrangements Square Large

Designed by Michael Anastassiades, 2018



34W - 1657lm - 2700K

Diffuse light suspended lighting device. Body in extruded, curved NC-machined and black powder-coated aluminium, diffuser in platinum optical silicone. Each component can be connected to the power pack by means of an electrical and mechanical connection system designed for customisable product set-up. Roses available with two powers: lamp with power under 70W and lamp with power under 190W. Class III roses also available for installations with remote power supply: "surface" version for installations on cement, "recessed" version for plasterboard ceilings. The electronics integrated in the rose enables use of dimming systems: push, 1-10, potentiometer, DALI. In the absence of these systems, the light flow can be set with the push system included in the rose. Cable length 2.4m



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

EAN	8059607014134
Mounting	Suspension
Environment	Indoor dry location
Light source type	LED
LED type	LED Module
Lamp holder	LED Module
Number of heads	1
Power (W)	34
System flux (lm)	1657

Physical

Colour	Black
Cord length (mm)	2500
Net weight (kg)	0.67
Package height (cm)	5
Package width (cm)	60
Package length (cm)	64
Package volume (m3)	0.02
IP	20
IP external	20

Download

[Mounting instructions](#) PDF

[Spare Parts](#) PDF

Photometric Files

[LDT / IES](#) LDT


Technical Drawings

[2D](#) ZIP

[3D](#) ZIP




Schematic light drawing



Ecodesign and Energy

Labelling

This product contains a light source of energy efficiency class F



Replaceable (LED only)
light source by a
professional


Photometric

Lighting type	Indirect, Direct
Light distribution	Symmetric
CCT (K)	2700

Electrical

Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	48
Driver	Remote
Dimmable	Yes
Dimming interface	Remote Dimmable (Dimmer Not Included)
Cord length (mm)	2500
Batteries inside	No
Charging min time	No

Accessories & Power Supply



REQUIRED

F0415030

Arrangements Big Rose



REQUIRED

F0418030

Arrangements Recessed Rose



REQUIRED

F0416030

Arrangements Small Rose