


FLOS

 F1070075 Brick Red

Bellhop Floor

Designed by Edward Barber and Jay Osgerby, 2020

26W - 1023lm - 2700K - CRI > 90



Floor lamp with indirect light. Stem in painted aluminium: shiny white, brick, cioko, green. Reflector in shiny opal white and grey blown glass. Electrical cable of 270 cm usable length with foot dimmer switch for ON/OFF function and brightness adjustment 10–100%. Power supply with interchangeable plugs.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

EAN	8059607039717
Mounting	Floor
Environment	Indoor dry location
Light source type	LED
LED type	LED array
Lamp holder	COB LED
Number of heads	1
Power (W)	26
System power (W)	26
System flux (lm)	1023

Physical

Colour	Brick Red
Length (mm)	260
Cord length (mm)	2700
Net weight (kg)	9.82
Package volume (m ³)	0.05
IP	20
IP external	20



Download

[Mounting instructions](#)  PDF

[Mounting instructions](#)  PDF

Photometric Files


[LDT / IES](#)  LDT

Technical Drawings

[3D](#)  ZIP



Schematic light drawing



Beam Angle:	33°		
h(m)	E(lx)	D(m)	
1	1474	0.59	
2	368	1.19	
3	164	1.78	
4	92	2.38	
5	59	2.97	

Photometric

Lighting type	Indirect
Light distribution	Roto symmetric
CCT (K)	2700
CRI >	90


Electrical

Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	100-240/48
LED current (mA)	700
Driver	Remote included
Dimmable	Yes
Dimming type	Electronic 12V
Dimming interface	Switch Integrated (Remote Dimmable)
Cord length (mm)	2700
Plug type	Type G, Type A, Type C
Batteries inside	No


Ecodesign and Energy

Labelling

This product contains a light source of energy efficiency class G



Replaceable (LED only) light source by a professional



Replaceable control gear by an end-user