

Bellhop Table

Designed by Edward Barber and Jay Osgerby, 2018


2.5W - 151lm - 2700K



Rechargeable direct light table lighting device. Base and dome in coloured PC. Diffuser in Opaline injection moulded photo-engraved PC. 24-hours' autonomy, charging via Micro-USB-C. Push-button switch positioned on the base provides the 4-step dimmer function. Battery status indicator positioned under the base. USB-C charging cable included, useful length 120cm. USB battery charging on plug with interchangeable plugs.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8059607001271
Mounting	Table
Enviroment	Indoor dry location
Light source type	LED
LED type	LED Module
Lamp holder	LED Module
Number of heads	1
Power (W)	2.5
System flux (lm)	151

Physical

Colour	White
Length (mm)	210
Net weight (kg)	1.3
Package height (cm)	20
Package width (cm)	20
Package length (cm)	33
Package volume (m3)	0.01
IP	20
IP external	20

Down	load
------	------

Mounting instructions	⊥ PDF
Spare Parts	业 PDF

Photometric Files

LDT / IES

₹ LDT

Technical Drawings

2D	$\overline{\mathbf{T}}$	ZIP
3D	$\overline{\uparrow}$	ZIP


















https://professional.flos.com/en/global/product/bellhop-table-f1060009/

F1060009

Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Roto symmetric
CCT (K)	2700

Electrical

Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	100-240/5
Driver	Remote included
Dimmable	Yes
Dimming type	Electronic 12V
Dimming interface	Dimmer Integrated
Plug type	Type G, Type A, Type C
Batteries inside	
Dattorio inolas	Yes
Battery type	Yes LI-PO
Battery type Charging max power	100
	LI-PO

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class C



Replaceable (LED only) light source by a professional



Replaceable control gear by an end-user

Spare Parts



RF1035109

Power charger with electrical cable & plugs