



Captain Flint Outdoor W1


Designed by Michael Anastassiades, 2020



Luminaire for wall-mounting with diffuse light emission and fixed head. LED light source included. Integrated 220-240V ON/OFF or 1-10V/DALI dimmable electrical power. Connection is quickly ensured in the rose with the plug & play electrical connection and the IP68 connector included. Clamp bracket included. 110V version upon request.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Ceiling and wall surface
LED type	LED array
Lamp category	LED
Number of heads	1
Power (W)	9.5
Source flux (lm)	989
System flux (lm)	629

Physical

Colour	Black
Trim	No
Orientation	Fixed
Recessed depth (mm)	0
Spot diameter (mm)	208
Length (mm)	336
Net weight (kg)	2.1
IP internal	65

Download

Mounting instructions

<u>↓</u> ZIP

Photometric Files

LDT / IES

₹ ZIP

Technical Drawings

2D	⊥ ZIP
3D	⊥ ZIP
a Bim	↓ ZIP









IP 65

Schematic light drawing



Beam Angle:		114
h(m)	E(lx)	D(n
1	217	3.0
2	54	6.1
3	24	9.1
4	14	12.2
	0	15.2

Luminous flux luminaire

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	80
Beam angle C0-180 (°)	112
Beam angle C90-270 (°)	112

Electrical

Insulation class	I
Frequency (Hz)	50-60
Main voltage (Vac)	220-240
Driver	Integrated
Dimmable	No
Dimming type	Non Dimmable
Precabled	no
Emergency type	No
Batteries inside	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Notes

110V version upon request.