

FLOS

F1583009 White

Clessidra 20°+20°

Designed by Antonio Citterio, 2011




2 x 10W - 2 x 637lm - 3000K

Diffused direct/indirect-light wall lighting device. Body obtained by means of aluminium pressofusion and diffusers in PMMA. Aluminium wall attachment with cover in PA66. Available in white-painted or chrome-plated for indoor version and dark brown-painted or dark gray-painted for outdoor version. High-efficiency lenses specially designed for the application, non-replaceable. Wide range (100-240Volt) power pack integrated in the body. Level IP55

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

EAN	8059607001493
Mounting	Wall
Environment	Indoor dry location
Light source type	LED
LED type	LED array
Lamp holder	COB LED
Number of heads	2
Power (W)	10
System flux (lm)	637

Physical

Colour	White
Net weight (kg)	1.1
IP	55
IP external	55

Download

[Mounting instructions](#) PDF

[Spare Parts](#) PDF

Photometric Files

[LDT / IES](#) ZIP


Technical Drawings

[2D](#) ZIP

[3D](#) ZIP



Schematic light drawing



Photometric

Lighting type	Indirect, Direct
Light distribution	Symmetric
CCT (K)	3000

Electrical


Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	100-240
Driver	Integrated
Batteries inside	No
Charging min time	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Spare Parts



F1580009

White external clessidra lamp
body



F1581030

Wall attachment and internal
lamp body 20°+20°



RF1580100

Screws and tool kit for clessidra
external lamp body