

FLOS

F1584009 White

Clessidra 40°+40°

Designed by Antonio Citterio, 2011




2 x 10W - 2 x 601lm - 3000K

Diffused direct/indirect-light wall lighting device. Body obtained by means of aluminium pressofusion and diffusers in PMMA. Aluminium wall attachment with cover in PA66. Available in white-painted or chrome-plated for indoor version and dark brown-painted or dark gray-painted for outdoor version. High-efficiency lenses specially designed for the application, non-replaceable. Wide range (100-240Volt) power pack integrated in the body. Level IP55

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)




Main specifications

EAN	8059607001547
Mounting	Wall
Environment	Indoor dry location
Light source type	LED
LED type	LED array
Lamp holder	COB LED
Number of heads	2
Power (W)	10
System flux (lm)	601

Physical

Colour	White
Net weight (kg)	1.1
IP	55
IP external	55

Download

[Mounting instructions](#)  PDF

[Spare Parts](#)  PDF

Photometric Files

[LDT / IES](#)  LDT


Technical Drawings

[2D](#)  ZIP

[3D](#)  ZIP



Schematic light drawing



The above drawing is for illustrative purposes only and refers to product code: F15840WWCLESSIDRA-40_10W-LED

Photometric

Lighting type	Indirect, Direct
Light distribution	Symmetric
CCT (K)	3000

Electrical


Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	100-240
Driver	Integrated
Dimming type	Non Dimmable
Batteries inside	No
Charging min time	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Spare Parts



F1580009

White external clessidra lamp
body



F1582030

Wall attachment and internal
lamp body 40°+40°



RF1580100

Screws and tool kit for clessidra
external lamp body