

FLOS

F1862033 Argent


Coordinates Suspension 2

Designed by Michael Anastassiades, 2020

55W - 2960lm - 2700K - CRI > 95



Coordinates is a lighting system with diffuse light composed of horizontal and vertical luminaires arranged in a bright grid of various shapes and complexities. Each element is made of extruded anodized aluminium with a champagne or argent finish and a diffuser in platinum optical silicone with an integrated LED strip (CRI 95). Each element is powered and supported by an invisible electrical and mechanical connection designed specifically to allow for the composition of the 4 hanging models (S1, S2, S3, S4) with 2.4-m cables. Each Coordinates configuration includes its own ceiling rose, whose integrated electronics allow for the use of different dimmer systems: push, 1-10, DALI. In the absence of these systems, the amount of light can be set during installation with the push system included in the rose.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

EAN	8059607038345
Mounting	Suspension
Environment	Indoor dry location
Light source type	LED
LED type	LED Module
Lamp holder	LED Module
Power (W)	55
Source flux (lm)	2960lm
System flux (lm)	2960

Physical

Colour	Argent
Length (mm)	1762
Cord length (mm)	2400
Net weight (kg)	2.7
Package volume (m3)	0.03
IP	20
IP external	20

Download

[Mounting instructions](#)  PDF

Photometric Files


[ULD](#)  ZIP

Technical Drawings

[3D](#)  ZIP



Schematic light drawing



Photometric

Lighting type	Total
Light distribution	Asymmetric
CCT (K)	2700
CRI >	95

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	120-240
Driver	Integrated
Dimming type	Dimmable 0-10V, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1
Cord length (mm)	2400
Batteries inside	No


Ecodesign and Energy

Labelling

This product contains a light source of energy efficiency class F



Replaceable (LED only)
light source by a
professional



Replaceable control
gear by a professional