

# FLOS

09.2112.05ADA Polished Aluminium

## Fort Knox Wall LED Dali Version

Designed by Philippe Starck, 2018




LED - Power LED - 32WW - 2676lm - 4000K - CRI> 90 - Beam° 39

Wall-mounted LED luminaire for indirect lighting. Power source incorporated into luminaire's body.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

Mounting	Wall surface
Environment	Indoor dry location
LED type	Power LED
Lamp category	LED
Icos	No
Number of heads	1
Power (W)	32W
Source flux (lm)	3714.69
System flux (lm)	2676

### Physical

Colour	Polished Aluminium
Trim	No
Orientation	Fixed
Net weight (kg)	1.40
IP	20
IP external	20

### Download

Mounting instructions [↓ PDF](#)

### Photometric Files

LDT / IES [↓ ZIP](#)


### Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)



## Schematic light drawing



Beam Angle:	39°	
h(m)	E(lx)	D(m)
1	778	3.39
2	194	6.77
3	86	10.16
4	49	13.55
5	31	16.94

Luminous flux Luminaire  
2676 lm

### Photometric

Lighting type	Indirect
Light distribution	Asymmetric
CCT (K)	4000
CRI >	90
Beam angle C0-180 (°)	39
Beam angle C90-270 (°)	62

### Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220.00
Driver	Integrated
Dimmable	Yes
Dimming type	Dimmable DALI 1
Emergency type	No