

FLOS

09.2127.40B White

Fort Knox Wall LED Mini


Designed by Philippe Starck



Wall-mounted LED luminaire for indirect lighting. Power source incorporated into luminaire's body.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)




Main specifications

Mounting	Wall surface
Environment	Indoor dry location
LED type	Power LED
Lamp category	LED
Icos	No
Number of heads	1
Power (W)	25W
System flux (lm)	2080

Physical

Colour	White
Trim	No
Orientation	Fixed
Net weight (kg)	0.6
IP	20
IP external	20


Download

[Mounting instructions](#)  PDF


Photometric Files

[LDT / IES](#)  ZIP


Technical Drawings

[2D](#)  ZIP

[3D](#)  ZIP



Schematic light drawing



Beam Angle: 33°

h(m)	E(lx)	D(m)
1	60	18.96
2	15	37.92
3	6	56.87
4	4	75.83
5	2	94.79

Photometric

Lighting type	Indirect
Light distribution	Asymmetric
CCT (K)	4000
CRI>	90
Beam angle C0-180 (°)	32
Beam angle C90-270 (°)	88

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220
Driver	Integrated
Dimmable	No
Dimming type	Non Dimmable
Emergency type	No

Notes

Mains Dimming under request.