


FLOS

F3150054 Natural


IPNOS OUTDOOR Anodized Natural

Designed by Nicoletta Rossi and Guido Bianchi, 2014



15W - N/Dlm - 3500K - CRI > 85

Floor lamp providing diffused light. Extruded aluminium frame 10x10x1 gratiné and anodized in various finishes. Leds on the top edges incorporated in the extrusions and burnished into the resin, guaranteeing the IP level. ON/OFF switch in the IP box containing the drivers. Two-pole spark-proof schuko plug.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

EAN	8059607017456
Mounting	Floor
Environment	Outdoor wet location
Light source type	LED
LED type	LED Module
Lamp holder	LED Module
Power (W)	15
System flux (lm)	N/D

Physical

Colour	Natural
Net weight (kg)	1.15
Package height (cm)	75
Package width (cm)	47
Package length (cm)	47
Package volume (m3)	0.16
IP	55
IP external	55

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)


Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)



Schematic light drawing



Beam Angle: 73°

h(m)	E(lx)	D(m)
1	337	1.49
2	84	2.98
3	37	4.47
4	21	5.96
5	13	7.44

Luminous flux Luminaire
744 lm

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3500
CRI>	85


Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	100-240
Plug type	Type C
Batteries inside	No
Charging min time	No


Ecodesign and Energy

Labelling

This product contains a light source of energy efficiency class F



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Accessories & Power Supply



OPTIONAL

F3125000

Ipnos Top Plate