



Kelvin Led Floor

Designed by Antonio Citterio, Antonio Citterio, 2011



8W - 285lm - 2700K

Floor lamp. Head in pressofused aluminium, diffuser in PC. Power pack on plug, base cover in injection printed PC, counterweight in iron cut and painted by means of a cataphoresic process. Directionable head. Three-step ON/OFF switch with Soft Touch technology. Base separated from the lamp body with safety locking pin.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

EAN	8059607003817
Mounting	Floor
Enviroment	Indoor dry location
Light source type	LED
LED type	LED Module
Lamp holder	LED Module
Number of heads	1
Power (W)	8
System flux (lm)	285

Physical

Colour	Black
Cord length (mm)	1500
Net weight (kg)	3.8
Package volume (m3)	0.04
IP	20
IP external	20



Mounting instructions	业 PDF
Mounting instructions	⊥ PDF
Spare Parts	⊥ PDF
Photometric Files	. ↓ . LDT
LDT / IES	⊥ LDT
	⊥ LDT



















https://professional.flos.com/en/global/product/kelvin-led-floor-f3305030/

F3305030

Schematic light drawing



Luminous flux luminaire

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700

Electrical

Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	100-240/24
Driver	Remote included
Dimming type	Electronic 12V
Cord length (mm)	1500
Plug type	Type G, Type A, Type C
Batteries inside	No
Charging min time	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Replaceable (LED only) light source by a professional



Replaceable control gear by an end-user

Spare Parts





Kelvin led gm black base



RF3320100

Black plug assembly kit & 24V driver



RF3320300

Kit with screw and allen keys



F3306030B

Kelvin led F black body