

# FLOS

■ F0288000 Black

## Noctambule Floor 1 Low Cylinder Small Base

Designed by Konstantin Grcic, 2019


18W - 485lm - 2700K



Standing lamps consisting of interconnecting glass modules reaching a height of 2,17 metres (85.43"). Cylindrical and semi-spherical transparent blown glass structure, die cast aluminium base and rings, hydroformed steel internal lateral arms and injection moulded optical opal silicone outer ring diffusers. The power supply cable is 2 metres (78.74") long, with a pedal operated panel used as a dimmer to adjust the light intensity by 10% to 100% in either direction. Wall mounted power supply unit with interchangeable plugs.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

|                   |                     |
|-------------------|---------------------|
| EAN               | 8059607000847       |
| Mounting          | Floor               |
| Environment       | Indoor dry location |
| Light source type | LED                 |
| LED type          | LED Module          |
| Lamp holder       | LED Module          |
| Power (W)         | 18                  |
| System flux (lm)  | 485                 |

### Physical


|                     |       |
|---------------------|-------|
| Colour              | Black |
| Net weight (kg)     | 10.3  |
| Package volume (m3) | 0.11  |
| IP                  | 20    |
| IP external         | 20    |

### Download

|                       |                       |
|-----------------------|-----------------------|
| Mounting instructions | <a href="#">↓ PDF</a> |
| Mounting instructions | <a href="#">↓ PDF</a> |
| Spare Parts           | <a href="#">↓ PDF</a> |



## Schematic light drawing



## Photometric

|                    |           |
|--------------------|-----------|
| Lighting type      | Total     |
| Light distribution | Symmetric |
| CCT (K)            | 2700      |


## Electrical

|                    |                        |
|--------------------|------------------------|
| Insulation class   | III                    |
| Frequency (Hz)     | 50/60                  |
| Main voltage (Vac) | 100-240/48             |
| Driver             | Remote included        |
| Dimmable           | Yes                    |
| Dimming type       | Electronic 12V         |
| Dimming interface  | Dimmer Integrated      |
| Plug type          | Type G, Type A, Type C |
| Batteries inside   | No                     |
| Charging min time  | No                     |


## Ecodesign and Energy

### Labelling

This product contains a light source of energy efficiency class E



Replaceable (LED only)  
light source by a  
professional



Replaceable control  
gear by an end-user

## Spare Parts



F0254000A

Noctambule Low Cylinder



F0261030A

Small base



F0293030A

Terminal cap



RF0254100

Fixing screws kit



RF27498

Ring led diffuser



RF27549

Switch dimmer 48v pmw 500hz



RF3320400

Black plug assembly kit & 48V driver