

Noctambule Suspension 6 High Cylinder


Designed by Konstantin Grcic, 2019

63W - 2096lm - 2700K

Hanging lamps consisting of interconnecting glass modules reaching a length of 3,2 mt. (126.77") with 4 mt. (157.48") suspended power cable. Cylindrical and semi-spherical transparent blown glass structure, suspended die cast aluminium ring connector, hydroformed steel internal lateral arm and injection moulded optical opal silicone outer ring diffusers. The power supply unit within the ceiling rose can be used as a dimmer to adjust the light intensity by 10% to 100% in either direction by means of the 0-10/1-10V, PUSH, DALI control.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8059607000779
Mounting	Suspension
Enviroment	Indoor dry location
Light source type	LED
LED type	LED Module
Lamp holder	LED Module
Power (W)	63
System flux (lm)	2096

Physical

Colour	Black
Cord length (mm)	4000
Net weight (kg)	26.9
Package volume (m3)	0.48
IP	20



Mounting instructions	↓ PDF
Mounting instructions	↓ PDF
Spare Parts	业 PDF

Photometric Files

LDT / IES



Technical Drawings

3D



















https://professional.flos.com/en/global/product/noctambule-suspension-6-high-cylinder-f0282000/

F0282000

Schematic light drawing



Photometric

Lighting type	Total
Light distribution	Symmetric
CCT (K)	2700

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	120-277
Driver	Integrated
Dimmable	Yes
Dimming type	Dimmable 0-10V, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1
Dimming interface	Remote Dimmable (Dimmer Not Included)
Cord length (mm)	4000
Batteries inside	No
Charging min time	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Spare Parts

