

# FLOS

F4640009 White

OK

Designed by Konstantin Grcic, 2014


18W - 1551lm - 2700K



Lamp providing direct light. Head in gloss varnished or chromed die-cast aluminium. Body in injection-stamped PA66+30%FV with cover in gloss varnished or chromed die-cast aluminium. Orientable head. The light fitting can be moved vertically by running the internal structure of the body on a steel cable tensioned between the ceiling and the floor (useful length 4000mm). Dimmable switch with Soft Touch technology. Adaptor on plug connector with interchangeable plugs.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



## Main specifications

EAN	8059607005057
Mounting	Suspension
Environment	Indoor dry location
Light source type	LED
LED type	LED Module
Lamp holder	LED Module
Number of heads	1
Power (W)	18
System flux (lm)	1551

## Physical

Colour	White
Cord length (mm)	4000
Net weight (kg)	2.9
Package height (cm)	14
Package width (cm)	34
Package length (cm)	39
Package volume (m3)	0.02
IP	20
IP external	20

## Download

Mounting instructions	↓ PDF
Mounting instructions	↓ PDF
Spare Parts	↓ PDF

## Photometric Files


LDT / IES	↓ LDT
-----------	-------

## Technical Drawings

2D	↓ ZIP
3D	↓ ZIP



## Schematic light drawing



Beam Angle: 61°

h(m)	E(lx)	D(m)
1	1158	1.19
2	289	2.38
3	129	3.57
4	72	4.76
5	46	5.95

## Photometric


Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700

## Electrical


Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	100-240/24
Driver	Remote included
Dimming type	Electronic 12V
Cord length (mm)	4000
Plug type	Type G, Type A, Type C
Batteries inside	No
Charging min time	No

## Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Replaceable (LED only) light source by a professional



Replaceable control gear by an end-user

## Spare Parts



RF23023

Counterweight



RF28253

White led head assembly



RF3320100

Black plug assembly kit & 24V driver



RF4640100

Anchor with hook



RF4640200

Steel cable 6mt.



RF4640300

Steel cable 6mt.



RF4640400

Internal lamp body assembly



RF06850

non c'è - ANDRA' IN  
SOSTITUZIONE DEL CODICE  
06850 NEI PROSSIMI  
AGGIORNAMENTI - LAMPADA  
"OK"



RF22998

White extrusion



RF23032

White ceiling rose