



Serena

Designed by Patricia Urquiola, 2015



15W - 643lm - 2700K - CRI> 90

Adjustable table lamp providing indirect and reflected light. Extruded aluminium heatsink, photoengraved black PC cut-off, photoengraved optical PMMA diffuser. Reflector in sheared and folded pre-anodized aluminium. Power cord length 200 cm, with dimmer switch that provides ON-OFF functions and 10-100% light adjustment. Plug-in power supply with interchangeable plugs

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

934 mm 248 mm 152 mm

Main specifications

EAN	8059607006610
Mounting	Table
Enviroment	Indoor dry location
Light source type	LED
LED type	LED Module
Lamp holder	LED Module
Number of heads	1
Power (W)	15
System flux (lm)	643

Physical

Colour	Black
Net weight (kg)	1.2
Package volume (m3)	0.02
IP	20
IP external	20

Download

Mounting instructions	⊥ PDF
Mounting instructions	⊥ PDF
Spare Parts	⊥ PDF

Photometric Files

LDT / IES



Technical Drawings

2D	1	$\overline{\mathbf{T}}$	ZIP
3D		V	ZIP

















https://professional.flos.com/en/global/product/serena-f6582030/

F6582030

Schematic light drawing



Luminous flux luminair

Photometric

Lighting type	Indirect
Light distribution	Asymmetric
CCT (K)	2700
CRI>	90

Electrical

Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	100-240/24
Driver	Remote included
Dimming type	Electronic 12V
Plug type	Type G, Type A, Type C
Batteries inside	No
Charging min time	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Replaceable (LED only) light source by a professional



Replaceable control gear by an end-user

Spare Parts









F6581030

Black leaf reflector

RF3320100

Black plug assembly kit & 24V driver

RF6580100

Kit with magnet for reflector

RF6605100

Jack plug with coaxial cable and dimmer