


# Skygarden 1

Designed by Marcel Wanders studio, 2007



Halogen - 105W

Suspension luminaire providing diffused lighting. Hemispherical, mechanically-processed cast plaster diffuser, painted white inside. Outer finish: rust, glossy black, glossy white or matte gold. Plaster diffuser support in die-cast aluminum alloy, liquid-painted white. Molded upper bushing in die-cast, polished aluminum alloy, protected with transparent paint on the entire visible part. Upper cable gland and blocking ring nut in black injection-molded PC (polycarbonate). Shaped, galvanized adjustment screws. Transparent, injection-molded, upper and lower silicone shock absorbers. Lamp holder and fixing support in black injection-molded PPS (polyphenylene sulfide). Flashed and blown opal glass diffuser. Molded fixing ring nut in die-cast aluminum alloy with alodine plating. Skygarden 1 frieze in photo-etched and mechanically drawn AISI 304 steel. Molded and galvanized steel ceiling attachment Gray, injection-molded PA6 (Nylon) rose.



Are you a professional and your project needs consulting and support?

**BOOK AN APPOINTMENT** 

Dlack

## Main specifications

EAN	8059607012758
Mounting	Suspension
Enviroment	Indoor dry location
Light source type	Bulb
Lamp category	Halogen
Lamp holder	E27
Ilcos	HSGS
Number of heads	1
Power (W)	105

### **Physical**

Colour	Віаск
Cord length (mm)	2700
Net weight (kg)	13
Package height (cm)	44
Package width (cm)	73
Package length (cm)	73
Package volume (m3)	0.23
IP	20
IP external	20

Mounting instructions	<b>业</b> PDF
Spare Parts	<b>业</b> PDF
Photometric Files	
LDT / IES	¥ LDT
Technical Drawings	
2D	<b>⊥</b> ZIP
3D	<u>↓</u> ZIP

https://professional.flos.com/en/global/product/skygarden-1-f0001030/

F0001030




















## Schematic light drawing



Beam Angle: 118° h(m) E(lx) D(m) 416 3.36 104 6.72 46 10.08 26 13.44 17 16.79

Luminous flux luminaire 2400 lm


#### **Photometric**

#### Lighting type Direct Light distribution Symmetric

## **Electrical**

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-250
Cord length (mm)	2700
Batteries inside	No
Charging min time	No

## **Bulbs**



**NOT INCLUDED** 

RF29388

LED T46 Lamp E27 20W 2700K Dimmable

# **Spare Parts**

RF05382 RF6410100 RF6410130

Kit of 5 or rings Skygarden 1 glass diffuser Black ceiling rose assembly

https://professional.flos.com/en/global/product/skygarden-1-f0001030/

F0001030