

FLOS

■ F0002031 Black


Skygarden 2

Designed by Marcel Wanders studio, 2007



Halogen - 205W

Suspension luminaire providing diffused lighting. Hemispherical, mechanically-processed cast plaster diffuser, painted white inside. Outer finish: rust, glossy black, glossy white or matte gold. Plaster diffuser support in die-cast aluminum alloy. Upper cable gland and blocking ring nut in black injection-molded PC. Shaped, adjustment screws. Transparent, injection-molded, upper and lower silicone shock absorbers. Lampholder and fixing support in PPS. Flashed and blown opal glass diffuser. Molded fixing ring nut in die-cast aluminum alloy with alodine plating. Frieze in photo-etched and mechanically drawn AISI 304 steel. Molded and galvanized steel ceiling attachment. Gray, injection-molded PC rose, painted the same color as the body.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)


Main specifications

EAN	8059607012918
Mounting	Suspension
Environment	Indoor dry location
Light source type	Bulb
Lamp category	Halogen
Lamp holder	E27
Ilcos	HSGS
Number of heads	1
Power (W)	205

Physical

Colour	Black
Cord length (mm)	2700
Net weight (kg)	0
IP	20
IP external	20

Download

[Mounting instructions](#)  PDF

[Spare Parts](#)  PDF

Photometric Files

[LDT / IES](#)  LDT

Technical Drawings

[2D](#)  ZIP

[3D](#)  ZIP



IP
20

<https://professional.flos.com/en/global/product/skygarden-2-f0002031/>


F0002031

©2022 Flos - P.IVA 00290820174 - 8/17/2022

professional.flos.com | info@flos.com 1/4

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order to improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.

Schematic light drawing



Beam Angle: 118°

h(m)	E(lx)	D(m)
1	729	3.36
2	182	6.72
3	81	10.08
4	46	13.44
5	29	16.79

Luminous flux luminaire
4210 lm

The above drawing is for illustrative purposes only and refers to product code: F64200XXWSKYGARDEN-2_230W-HL

Photometric

Lighting type	Direct
Light distribution	Symmetric

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-250
Cord length (mm)	2700
Batteries inside	No
Charging min time	No

Bulbs



NOT INCLUDED

RF29388

LED T46 Lamp E27 20W 2700K

Dimmable

Spare Parts



RF05382

Kit of 5 rings



RF6420100

Glass diffuser assembly



RF6420331

Opal black ceiling rose assembly