



Wireline

Designed by Formafantasma, 2019



45W - 2793lm - 2700K - CRI> 90

Suspension lamp with diffused light. Tubular in transparent extruded glass and internal diffuser in opal PC. Ferrules made with CNC technology in satin stainless steel. Extruded cable in pink and forest green rubber. Injection molded PC rosette in the same finishes as the cable. The electronics integrated in the ceiling rose allows the use of different dimerization systems: push, 1-10, potentiometer, DALI. In the absence of these systems, the luminous flux can be set during installation, with the push system included in the canopy. Useful length of the cable 3mt.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

EAN	8059607034545
Mounting	Suspension
Enviroment	Indoor dry location
Light source type	LED
LED type	LED Module
Lamp holder	LED Module
Number of heads	1
Power (W)	45
System power (W)	45
System flux (lm)	2793

Physical

Colour	Green
Length (mm)	1300
Cord length (mm)	2000/4050
Net weight (kg)	7.8
Package volume (m3)	0.05
IP	20
IP external	20



Download Mounting instructions	≱ PDF
Photometric Files	⊥ LDT
Technical Drawings 3D	⊥ ZIP















https://professional.flos.com/en/global/product/wireline-f9520039/

F9520039

Schematic light drawing



Luminous flux luminair

The above drawing is for illustrative purposes only and refers to product code: F95200WWIRELINE_45W-LED

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Photometric

Lighting type	Total
Light distribution	Symmetric
CCT (K)	2700
CRI>	90

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	120-277
Driver	Integrated
Dimming type	Dimmable 0-10V, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1
Cord length (mm)	2000/4050
Batteries inside	No