

FLOS

 F9514030 Pink Cable/Black Ring

Wirering Pink

Designed by Formafantasma, 2018


16W - 712lm - 2700K - CRI > 90



Indirect light wall lighting device with body in calendered, extruded aluminium with galvanised or varnished finish. The special tangent cable, in coloured rubber, provides the power. The cable is fixed to the wall with ABS joints in the same finish as the ring. Dimming via switch pedal on the cable. Power supply on adapter with interchangeable plugs. Useful cable length is 2.5 metres.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)




Main specifications

EAN	8059607007792
Mounting	Wall
Environment	Indoor dry location
Light source type	LED
LED type	LED Module
Lamp holder	LED Module
Number of heads	1
Power (W)	16
System flux (lm)	712

Physical

Colour	Pink Cable/Black Ring
Length (mm)	317
Cord length (mm)	2500
Net weight (kg)	0.95
Package volume (m ³)	0.02
IP	20
IP external	20

Download

[Mounting instructions](#)  PDF

[Spare Parts](#)  PDF

Photometric Files

[LDT / IES](#)  LDT


Technical Drawings

[2D](#)  ZIP

[3D](#)  ZIP



Schematic light drawing



Photometric

Lighting type	Indirect
Light distribution	Asymmetric
CCT (K)	2700
CRI >	90

Electrical


Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	100-240/24
Driver	Remote included
Dimming type	Electronic 12V
Cord length (mm)	2500
Plug type	Type G, Type A, Type C
Batteries inside	No
Charging min time	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Replaceable (LED only) light source by a professional



Replaceable control gear by an end-user

Spare Parts



RF26646

Electrical mounting assembly with dimmer



RF26651

Electrical mounting body assembly



RF26678

Ring assembly



RF3320100

Black plug assembly kit & 24V driver



RF9510500

Kit with screws, nuts and components