## Algorithm




Design By Toan Nguyen

Pendant light fitting designed by Toan Nguyen. Composed of a collection of hand-blown glass spheres with LED light source suspended at different heights, anchored to the ceiling via a floating tubular structure.

## Spec sheet







Optional: Extra cable length Min. Quantity, upcharge and extra lead time apply

Finish

18 Graphite ADAPTA RF 9913 WX



93 White RAL 9016

I.ED color temperature 2700 K

Dimmina

0-10V

DALI or Lutron ECO Optional Min. Quantity, upcharge and extra

lead time apply

Installation type

Surface mounted

Materials

Sphere: Blown glass Pendant structure: Steel Canopy: Steel

Diffuser: Polycarbonate

Light source

29 x LEDN 3.15W 1050mA

LED

CRI>90 9056.12 lm 99.14

2700 K

Driver

CC - Constant Current 1050 120~277 V 50/60 HZ

Remarks

The steel cables that go from the structure to the ceiling are the only ones that allow the height of the lamp to be adjusted. The installation manual describes how to do this and how to cut the


cables.

Optional 10 inches stems included.

Dimmable LED IP20 Multi-volt









**Pendants** 

**Packaging** 

26.38 m x 23.23 m x 21.26 m

Gross weight 57.27 Net weight 44.93 Vol. 22.086

Lighting effect

**General Lighting** 

Lamp for general lighting that equally distributes the light in all directions.



Photometric Data

Efficiency Coordination System **Total Flux** Maximum Value

80.04% CG 9056.12 lm 197.21 cd/klm

Other Applications

