






Design By Umut Yamac

The hanging Array lamp combines a series of fine technical filaments between two rings. The indirect lighting rises through the cylindrical form creating a colour gradient.

Model Sheet







Optional : Extra cable length Min. quantity, upcharge and extra lead time apply [EN]

Finish

24 Beige M1 NCS S 2005-Y50R

47 Green L1 NCS S 4005-G80Y

37 Terra Red NCS S 4040-Y70R

LED temperature

2700 K

Dimming

Push; DALI / 1-10V / Casambi

Instalation type

Surface Canopy / Remote Micro /

Built-in S

Materials

Upper ring: Aluminum Bottom ring: Brass Diffuser: PC- Polycarbonate

Threads: PES FR

Light source

1x LED STRIP 76W 48V

D

LED

CRI>90 9196 lm 121

2700 K

Driver

Constant Voltage 90~305 V V

50~60 Hz HZ

Dimmable [IP20] [Multi-volt]

50-60Hz 1-10V

Application

Hanging lamps

Packaging

1 Box

0.12 m x 1.35 m x 1.35 m Gross weigth 23 Net weigth 13 Vol. 0.2187

Lighting effect

General lighting

Lamp for general lighting that equally distributes the light in all directions.

Photometric Data

Other Applications



All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty