




Design By Lievore Altherr Molina

Accessible ceiling light for indoor use, designed by Lievore, Altherr, Molina. Direct, diffuse, and uniform light distribution. Chrome or matte white lacquer body and white opal methacrylate diffuser. Its large size makes it ideal for lighting large spaces from a single point.

Spec sheet







93 White RAL 9010 01 Chrome Chromeplated

LED color temperature 3500 K

0-10V Dimming

Optional DALI or Lutron ECO Min. Quantity, upcharge and extra

lead time apply

Installation type Surface mounted

Materials Shade: Aluminum

Diffuser: Acrylic Ring: Steel Canopy: Steel

Light source 4 x LED Quadrant 18.9W 500mA

LED CRI>90 8969.8 lm 118.65

3500 K

CC - Constant Current 500 Driver

120~277 V 50/60 HZ

Dimmable LED [IP20] [Multi-volt]

© Dry Location 50-60Hz

Application Ceiling Fixtures

Packaging

53.15 m x 53.15 m x 14.96 m Gross weight 46.26 Net weight 41.63 Vol. 24.4556

Lighting effect

General Lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric Data

Efficiency Coordination System **Total Flux** Maximum Value

70.01 lm/W CG 5638.14 lm 1897.01 cd