




Design By Lievore Altherr Molina

Pendant for indoor use, designed by Lievore, Altherr, Molina. Direct, diffuse, and uniform light distribution. Chrome body and white opal methacrylate diffuser with an opaque shade which therefore projects more light downwards.

Spec sheet



Optional: Extra cable length
Min. Quantity, upcharge and extra lead time apply

Finish	<ul style="list-style-type: none">  01 Chrome Chromeplated  93 White RAL 9010
LED color temperature	3500 K
Dimming	0-10V Optional DALI or Lutron ECO Min. Quantity, upcharge and extra lead time apply
Installation type	Surface mounted
Materials	Shade: Aluminum Diffuser: Acrylic Ring: Steel Canopy: Steel
Light source	4 x LED Quadrant 18.9W 500mA A+
LED	CRI>90 8969.8 lm 118.65 3500 K
Driver	CC - Constant Current 500 120-277 V 50/60 HZ

Dimmable LED IP20 Multi-volt
UL Dry Location 50-60Hz 0-10V

Application	Pendants
Packaging	1 Box 44.09 m x 44.09 m x 13.58 m Gross weight 43.17 Net weight 38.85 Vol. 15.2808

Lighting effect

General Lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric Data

Efficiency	94.82 lm/W
Coordination System	CG
Total Flux	6904.01 lm
Maximum Value	2359.46 cd