


## 4878

Design By Ramos & Bassols

The collection DUO is inspired by sustainability and wellness. This flush-mount surface light is designed for places with a lower ceiling. The inner surface of the shade is lined with oak veneer, enveloped in a matte lacquered outer shell constructed of aluminum. The LED light source provides even illumination with its polycarbonate diffuser. DUO is available in three finishes.

### Spec sheet



<b>Finish</b>	<ul style="list-style-type: none"> <li><span style="display: inline-block; width: 10px; height: 10px; background-color: white; border-radius: 50%; margin-right: 5px;"></span> 93 White RAL 9016</li> <li><span style="display: inline-block; width: 10px; height: 10px; background-color: black; border-radius: 50%; margin-right: 5px;"></span> 18 Graphite ADAPTA RF 9913 WX</li> <li><span style="display: inline-block; width: 10px; height: 10px; background-color: #c8c8c8; border-radius: 50%; margin-right: 5px;"></span> 58 Cream RAL 7044</li> </ul>
<b>LED color temperature</b>	2700 K
<b>Dimming</b>	0-10V <b>Optional</b> DALI or Lutron ECO Min. Quantity, upcharge and extra lead time apply
<b>Installation type</b>	Surface mounted


<b>Materials</b>	Body: Aluminum Shade: Oak wood Canopy: Aluminum
<b>Light source</b>	1 x LED PLATE 26W 500mA
<b>LED</b>	CRI>90 1284 lm 74.9 2700 K
<b>Driver</b>	CC - Constant Current 500 100-277 V 50/60 HZ

Dimmable
LED
IP20
Multi-volt  
UL
Dry Location
50-60Hz
0-10V

#### Lighting effect

##### General Lighting

Lamp for general lighting that equally distributes the light in all directions.



#### Photometric Data

<b>Efficiency</b>	100%
<b>Coordination System</b>	CG
<b>Total Flux</b>	1284.41 lm
<b>Maximum Value</b>	727.04 cd

<b>Application</b>	Ceiling Fixtures
<b>Packaging</b>	1 Box 23.35 m x 30.91 m x 30.91 m Gross weight 35.24 Net weight 30.84 Vol. 12.9041