Funnel

\vee |] | \wedge

2014

Design By undefined

Light for ceiling or wall fitting. Gives an indirect light which is ideal for creating a cosy atmosphere in any room. Non-dazzle.

Model Sheet Finish 36 Soft Pink Lighting effect NCS S 1010-Y50R **General Lighting** 47 Green L1 Lamp for general lighting that equally distributes NCS S 4005-G80Y the light in all directions. 10 White NCS S 0300-N LED temperature 2700 K color Dimming DALI 1-10V Push Casambi Optional Photometric Data Min. quantity, upcharge and extra lead time apply [EN] Other Applications Surface Canopy Instalation type Materials Shade: Aluminum Reflector: Aluminum Wall plate: Steel Light source 6 x LED 4,48W 350mA Е LED CRI>90 2700 K CC - Constant Current 350 Driver 110~240 V 50/60 HZ ↓ F Dimmable LED IP20 Bi-volt 50-60Hz Application Ceiling Lamps ø 50 cm Packaging 1 Box 0.6 m x 0.6 m x 0.27 m 13 cm Gross weigth 2.65 Net weigth 2.1 Vol. 0.0972 ø 16 cm

All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty

Vibia Lighting, S.L.U.

Office / Oficina Progrés 4-6. 08850 Gavà. Barcelona, Spain.