Guise



2294

Design By Diez Office

Ceiling LED lamp. The light is diffused in an almost invisible manner through the glass and only emerges through the striations etched on the surface, diffusing the light as if by magic.

Spec sheet









LED color temperature 3000 K

Dimming 1-10V

Optional DALI or Lutron ECO Min. Quantity, upcharge and extra

lead time apply

Installation type Surface mounted

Materials Canopy: Steel
Body: Aluminum

Light source 1 x LED STRIP 24V 12W

Α+

LED CRI>90 1325 lm 89.08

3000 K

Driver CV - Constant Voltage [object

Object] 110~240 V 50/60 HZ

Remarks The glass is made of borosilicate. It is typical for the glass to have

satypical for the glass to have small air bubbles, some inclusions and tiny scratches. These do not affect the quality or the resistance

of the glass.

Dimmable LED

, , ,

IP20 Bi-volt Dry Location

50-60Hz **1-10V**

Application Ceiling Fixtures

Packaging 1 Box

18.9 m x 14.96 m x 14.96 m Gross weight 13.44 Net weight 11.23 Vol. 2.4473

Lighting effect

General Lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric Data

Efficiency 100%
Coordination System CG
Total Flux 472.92 lm
Maximum Value 196.63 cd

VIBIA, INC.