Guise



2298

Design By Diez Office

Ceiling LED lamp. The light is diffused in an almost invisible manner through the glass and only emerges through the striations etched on the surface, diffusing the light as if by magic.

Spec sheet









LED color temperature 3000 K

Dimming 1-10V

Optional DALI or Lutron ECO Min. Quantity, upcharge and extra

lead time apply

Installation type Surface mounted

Materials Canopy: Steel
Body: Aluminum

Light source 1 x LED STRIP 24V 18W

Α+

LED CRI>90 1325 lm 73.61

3000 K

Driver CV - Constant Voltage [object

Object] 90~305 V 50/60 HZ

Remarks The glass is made of borosilicate. It

is typical for the glass to have small air bubbles, some inclusions and tiny scratches. These do not affect the quality or the resistance

of the glass.

Dimmable LED

 $\fbox{IP20} \hspace{0.1cm} \fbox{Multi-volt} \hspace{0.1cm} {}_{c} \textcolor{red}{\textcolor{blue}{\mathbb{Q}}_{L}} \textcolor{blue}{\textbf{Us}} \hspace{0.1cm} \boxed{\textbf{Dry Location}}$

50-60Hz **1-10V**

Application Ceiling Fixtures

Packaging 1 Box

21.26 m x 21.26 m x 16.54 m Gross weight 29.3 Net weight 24.89 Vol. 4.3226 Lighting effect

General Lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric Data

Efficiency 100%
Coordination System CG
Total Flux 868.47 lm
Maximum Value 348.73 cd