Halo jewel



2356

Design By Martín Azúa

Pendant light, providing an ambient or indirect light through its vertical methacrylate diffuser. The diffuser is supported by a fine-grade steel structure. The back part of the diffuser in steel is finished in either a gold or black color, lending it a clean decorative aesthetic.

Spec sheet







Optional: Extra cable length Min. Quantity, upcharge and extra lead time apply



Black NCS S 8500N



20 Gold finish

LED color temperature 3000 K

Dimmina

0-10V DALI

Optional

Min. Quantity, upcharge and extra

lead time apply

Installation type

Surface mounted

Materials

Diffuser: Acrylic LED support: Aluminum Pendant structure: Steel Canopy: Steel

Light source

3 x LED STRIP 24V 15,3W

LED

CRI>80 4584.12 lm 99.87 3000 K


Driver

CV - Constant Voltage [object Object] 120~277 V 50/60 HZ

Remarks

Surface Mounted













Application

Pendants

Packaging

78.74 m x 12.99 m x 12.2 m Gross weight 16.3 Net weight 13.35 Vol. 7.2254

Lighting effect

General Lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric Data

Efficiency Coordination System **Total Flux** Maximum Value

100 % CG 3470.39 lm 697.50 cd