## Musa

## $\vee$ | 3 | $\wedge$

Lighting effect General Lighting

Photometric Data Efficiency Coordinate System

Other Applications

Total Flux Maximum Value

Lamp for general lighting that equally distributes the light in all directions.

44.11 lm/W CG 103.22 lm

23.46 cd

## 7404

Design By Note Design Studio

Vibia offers a table lamp. The aluminum base captures the light as the small glass sphere and transforms it into a soft illumination.

## Model Sheet





ø 10 1/4°

Finish	<b>93 White</b> RAL 9016
	36 Soft Pink NCS S 1010-Y50R
	24 Beige M1 NCS S 2005-Y50R
LED temperature color	2700 K
Dimming	Push
Instalation type	Surface Canopy
Materials	Body: Aluminum Diffuser: Blown-glass
Light source	1 x LED 1,5W 500mA G
LED	CRI>90 156.94 lm 104 2700 K
Driver	CV - Constant Voltage 100~240 V 50/60 HZ
Remarks	Dimmer switch on the base. 3 step dimming. Battery life: from 6 to 18 hours (depending on intensity). (Depending on intens
Application	Table Lamps
Packaging	1 Box 0.32 m x 0.29 m x 0.169 m Gross weigth 1.4 Net weigth 0.95 Vol. 0.0156

All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty

Vihia	Lighting,	5111
VIDIU	Lighting,	J.L.U.

5 1/2"

Office / Oficina Progrés 4-6. 08850 Gavà. Barcelona, Spain.