


2632

Design By Arik Levy

Ceiling light with basic lines and cubic volumes that form sculptures integrated into the architecture.

Model Sheet




Finish	<div style="display: flex; gap: 10px;"> <div style="display: flex; align-items: center;"> 15 Grey L2 NCS S 2500-N </div> <div style="display: flex; align-items: center;"> 21 Black Grey </div> </div>
LED temperature color	3000 K
Dimming	1-10V Optional DALI or Casambi Min. quantity, upcharge and extra lead time apply [EN]
Installation type	Surface Canopy
Materials	Body: Aluminum Diffuser: Polycarbonate Profile: Aluminum
LED	CRI>90 3000 K
Driver	CV - Constant Voltage 110-240 V 50/60 HZ
Remarks	Main input by the biggest box
	<div style="display: flex; gap: 5px; align-items: center;"> Dimmable LED </div> <div style="display: flex; gap: 5px; align-items: center; margin-top: 5px;"> IP20 Bi-volt 50-60Hz </div>
Application	Ceiling Lamps
Packaging	1 Box 0.24 m x 0.38 m x 0.38 m Gross weight 3.3 Net weight 2.8 Vol. 0.0346

Lighting effect

General Lighting


Lamp for general lighting with an opaque shade and distributing light upwards and/or downwards mainly.



Photometric Data

Efficiency	68.54 lm/W
Coordinate System	CG
Total Flux	1507.91 lm
Maximum Value	660.02 cd

Other Applications



All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty

Vibia Lighting, S.L.U.

Office / Oficina
Progrés 4-6. 08850 Gavà. Barcelona, Spain.

International T +34 934 796 971
Spain / Portugal T +34 934 796 970

customer.service@vibia.com
vibia.com