


## 5763

Design By Lievore Altherr

Wall lamp composed of a stylized profile attached to the wall and topped by a blown glass diffuser that gives the piece a delicate image. Connection without a plug. LED light source.

### Spec sheet




<b>Finish</b>	<ul style="list-style-type: none"> <li><span style="display: inline-block; width: 10px; height: 10px; background-color: black; border-radius: 50%; margin-right: 5px;"></span> 18 Graphite ADAPTA RF 9913 WX</li> <li><span style="display: inline-block; width: 10px; height: 10px; background-color: #808080; border-radius: 50%; margin-right: 5px;"></span> 62 Green NCS S 3010-G20Y</li> <li><span style="display: inline-block; width: 10px; height: 10px; background-color: #800000; border-radius: 50%; margin-right: 5px;"></span> 37 Terra Red NCS S 4040-Y70R</li> </ul>
<b>LED color temperature</b>	2700 K
<b>Dimming</b>	0-10V <b>Optional</b> DALI or TRIAC Min. Quantity, upcharge and extra lead time apply
<b>Installation type</b>	Recessed

<b>Materials</b>	Body: Steel Diffuser: Blown-glass LED support: Aluminum
<b>Light source</b>	1 x LED 4W 350mA A++
<b>LED</b>	CR>90 440.81 lm 110 2700 K
<b>Driver</b>	CC - Constant Current 350 120-277 V 50/60 HZ
<b>Remarks</b>	Recessed

LED
IP20
Multi-volt
UL
Dry Location
50-60Hz
0-10V

<b>Application</b>	Wall Fixtures
<b>Packaging</b>	3 Box 15.12 m x 57.28 m x 2.83 m Gross weight 12.56 Net weight 7.93 Vol. 2.1366

<b>Lighting effect</b>	
<b>General Lighting</b>	Lamp for general lighting that equally distributes the light in all directions.
	
<b>Photometric Data</b>	
<b>Efficiency</b>	100%
<b>Coordination System</b>	CG
<b>Total Flux</b>	301.62 lm
<b>Maximum Value</b>	235.37 cd