Tempo



5767


Design By Lievore Altherr

Wall lamp composed of a stylized profile attached to the wall and topped by a blown glass diffuser that gives the piece a delicate image. Connection without a plug. LED light source.

Spec sheet







62 Green NCS S 3010-G20Y 18 Graphite ADAPTA RF 9913 WX 37 Terra Red NCS S 4040-Y70R

LED color temperature 2700 K

Dimming 0-10V

Optional DALI or TRIAC Min. Quantity, upcharge and extra lead time apply

Installation type Recessed

Materials Body: Steel

Diffuser: Blown-glass LED support: Aluminum

Light source 1 x LED 4W 350mA

A++

LED CRI>90 440.81 lm 110

2700 K

Driver CC - Constant Current 350

120~277 V 50/60 HZ

Remarks Recessed

[LED] [IP20] [Multi-volt] [Dry Location]

50-60Hz

Application Wall Fixtures

Packaging 3 Box

15.12 m x 57.28 m x 2.83 m Gross weight 11.23 Net weight 6.61 Vol. 2.1366

Lighting effect

General Lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric Data

Efficiency 100%
Coordination System CG
Total Flux 302.04 lm
Maximum Value 203.44 cd

VIBIA, INC.