

Tube


VIBIA

6100

Design By Ichiro Iwasaki

Ceiling lamp defined by its curved sheet aluminum shade lending a visual and material lightweight quality. Size selection from 11 1/4 to 20 1/2 in diameters with 4 different finishes, white and three greys.

Spec sheet



Finish

- 10 White
NCS S 0300-N
- 16 Grey M1
NCS S 4500-N
- 21 Black Grey
NCS S 7000-N
- 15 Grey L2
NCS S 2500-N

LED color temperature 2700 K

Dimming 0-10V
Optional DALI or Lutron ECO
Min. Quantity, upcharge and extra lead time apply

Installation type Surface mounted

Materials LED support: Aluminum
Canopy: Steel

Light source 1 x LED PLATE 13.5W 700mA
A+

LED CRI>90 1740 lm 128.8
2700 K

Driver CC - Constant Current 700
120-277 V 50/60 HZ

Dimmable LED IP20 Multi-volt

UL Dry Location 50-60Hz 0-10V

Application Ceiling Fixtures

Packaging 1 Box
9.76 m x 15.87 m x 15.87 m
Gross weight 6.61
Net weight 3.08
Vol. 1.4197

Lighting effect

General Lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric Data

Efficiency 39.65 lm/W
Coordination System CG
Total Flux 631.96 lm
Maximum Value 259.67 cd

VIBIA, INC.

USA & CANADA
272 Fernwood Ave. Edison, NJ 08837. USA
Phone 732 417 1700 sales@vibia.com www.vibia.com/us/usa

HEADQUARTERS
Progrés 4-6. 08850 Gavà
(Barcelona - Spain)