


## 6110

Design By Ichiro Iwasaki

Ceiling lamp defined by its curved sheet aluminum shade lending a visual and material lightweight quality. Size selection from 11 1/4 to 20 1/2 in diameters with 4 different finishes, white and three greys.

### Spec sheet



<b>Finish</b>	<ul style="list-style-type: none"> <li><span style="display: inline-block; width: 10px; height: 10px; background-color: #f0f0f0; border-radius: 50%; margin-right: 5px;"></span> 10 White NCS S 0300-N</li> <li><span style="display: inline-block; width: 10px; height: 10px; background-color: #333333; border-radius: 50%; margin-right: 5px;"></span> 21 Black Grey NCS S 7000-N</li> <li><span style="display: inline-block; width: 10px; height: 10px; background-color: #666666; border-radius: 50%; margin-right: 5px;"></span> 16 Grey M1 NCS S 4500-N</li> <li><span style="display: inline-block; width: 10px; height: 10px; background-color: #999999; border-radius: 50%; margin-right: 5px;"></span> 15 Grey L2 NCS S 2500-N</li> </ul>
---------------	---

**LED color temperature** 2700 K

**Dimming** 0-10V  
**Optional** DALI or Lutron ECO  
 Min. Quantity, upcharge and extra lead time apply

**Installation type** Surface mounted

**Materials** LED support: Aluminum  
 Canopy: Steel

**Light source** 1 x LED PLATE 20W 700mA  
 A+

**LED** CRI>90 2900 lm 145  
 2700 K

**Driver** CC - Constant Current 700  
 120-277 V 50/60 HZ

Dimmable LED IP20 Multi-volt

UL Dry Location 50-60Hz 0-10V

**Application** Ceiling Fixtures

**Packaging** 1 Box  
 14.65 m x 25.71 m x 25.71 m  
 Gross weight 15.64  
 Net weight 8.37  
 Vol. 5.601

#### Lighting effect

##### General Lighting

Lamp for general lighting that equally distributes the light in all directions.



#### Photometric Data

<b>Efficiency</b>	51.14 lm/W
<b>Coordination System</b>	CG
<b>Total Flux</b>	1243,11 lm
<b>Maximum Value</b>	494,85 cd