Wireflow

\vee | 3 | \wedge

0307

Design By Arik Levy

Wireflow designed by Arik Levy. A hanging lamp which reviews and updates the chandelier look through an exercise of simplification that explores its essence and enhances its outline with great delicacy and at the same time a strong formal presence. Its appearance, as a structure of fine cables finished with eight LED terminals, discretely connects with classic chandelier models, taking this type of lamp to a new, groundbreaking and futuristic dimension. Employing CREA product configurator software, the design can be modified to adapt to your specific project requirements.

Model Sheet





Image: Color 2700 K Dimming DALI 1-10V Push Optional Casambi Min. quantity, upcharge and extra lead time apply [EN] Instalation type Surface Canopy Materials Ceiling rose: Steel Body: Aluminum Horizontal rods: Steel Light source 6 x LED 4,48W 350mA D LED CRI>80 2942 lm 108 2700 K Driver CC - Constant Current 350 110-240 V 50/60 HZ Imable LED Imable LED Imable ED Imable ED CRI>80 2942 lm 108 2700 K D ED LED CRI>80 2942 lm 108 2700 K Driver CC - Constant Current 350 110-240 V 50/60 HZ Imable LED Imable LED </th <th>Finish</th> <th></th>	Finish	
Dimming DALI 1-10V Push Optional Casambi Min. quantity, upcharge and extra lead time apply [EN] Instalation type Surface Canopy Materials Ceiling rose: Steel Body: Aluminum Horizontal rods: Steel Light source 6 x LED 4,48W 350mA D LED CRI>80 2942 lm 108 2700 K Driver CC - Constant Current 350 110-240 V 50/60 HZ Imable LED IP20 Bi-volt IP20 Bi-volt Application Hanging lamps Packaging 2 Box 0.6 m x 0.6 m x 0.27 m Gross weigth 9.6 Net weigth 8.64	Finish	O4 Black RAL 9005
Optional Casambi Min. quantity, upcharge and extra lead time apply [EN] Instalation type Surface Canopy Materials Ceiling rose: Steel Body: Aluminum Horizontal rods: Steel Light source 6 x LED 4,48W 350mA D LED CRI>80 2942 lm 108 2700 K Driver CC - Constant Current 350 110-240 V 50/60 HZ IP20 Bi-volt [P20] Bi-volt Application Hanging lamps Packaging 2 Box 0.6 m x 0.27 m Gross weigth 9.6 Net weigth 8.64	LED temperature color	2700 K
Materials Ceiling rose: Steel Body: Aluminum Horizontal rods: Steel Light source 6 x LED 4,48W 350mA D LED CRI>80 2942 lm 108 2700 K Driver CC - Constant Current 350 110-240 V 50/60 HZ Image: Steel Image: Steel Image: Steel Image: Steel Application Hanging lamps Packaging 2 Box 0.6 m x 0.6 m x 0.27 m Gross weigth 9.6 Net weigth 8.64	Dimming	Optional Casambi Min. quantity, upcharge and extra
Body: Aluminum Horizontal rods: Steel Light source 6 x LED 4,48W 350mA D LED CRI>80 2942 lm 108 2700 K Driver CC - Constant Current 350 110~240 V 50/60 HZ Image: Protein Street IP20 Bi-volt 50-60Hz Packaging 2 Box 0.6 m x 0.6 m x 0.27 m Gross weigth 9.6 Net weigth 8.64	Instalation type	Surface Canopy
D LED CRI>80 2942 lm 108 2700 K Driver CC - Constant Current 350 110~240 V 50/60 HZ	Materials	Body: Aluminum
2700 K Driver CC - Constant Current 350 110-240 V 50/60 HZ	Light source	
110-240 V 50/60 HZ	LED	
IP20 Bi-volt 50-60Hz Application Hanging lamps Packaging 2 Box 0.6 m x 0.6 m x 0.27 m Gross weigth 9.6 Net weigth 8.64	Driver	
Packaging 2 Box 0.6 m x 0.6 m x 0.27 m Gross weigth 9.6 Net weigth 8.64		
0.6 m x 0.6 m x 0.27 m Gross weigth 9.6 Net weigth 8.64	Application	Hanging lamps
	Packaging	0.6 m x 0.6 m x 0.27 m Gross weigth 9.6 Net weigth 8.64

Lamp for general lighting that equally distributes the light in all directions.

Lighting effect General Lighting

Photometric Data Efficiency Coordinate System


Total Flux

40.11% CG 2941.60 53.87

Other Applications

Maximum Value





Optional : Extra cable length Min. quantity, upcharge and extra lead time apply [EN]

All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty

Vibia Lighting, S.L.U.

Office / Oficina Progrés 4-6. 08850 Gavà. Barcelona, Spain. International T +34 934 796 971 Spain / Portugal T +34 934 796 970

customer.service@vibia.com vibia.com