Wireflow free-form

0345

Design By Arik Levy

Wireflow designed by Arik Levy. Hanging Iap. The elegant structure of fine cables and LED terminal by Wireflow allows the combination of multiple individual pieces to carry out major graphic lighting installations which generate a visual opportunity of lines and points of light and bring a markedly conceptual character to an intangible product. Employing CREA product configurator software, the design can be modified to adapt to your specific project requirements. The electrical connection point can be positioned on the ceiling or wall

Model Sheet



Finish	04 Black	Lighting effect
	RAL 9005	General Lighting
LED temperature color	2700 K	Lamp for general the light in all dire
Dimming	1-10V PUSH Optional DALI or Casambi Min. quantity, upcharge and extra lead time apply [EN]	
Instalation type	Surface Canopy	
Materials	Rods: Steel Body: Aluminum Ceiling rose: Steel	Photometric Data Efficiency Coordinate Syste Total Flux Maximum Value
Light source	1 x LED 4,5W 700mA D	
LED	CRI>90 490 lm 109 2700 K	
Driver	CC - Constant Current 700 100~240 V 50/60 HZ	
	Dimmable LED IP20 Bi-volt 50-60Hz	
Application	Hanging lamps	
Packaging	1 Box 0.26 m x 0.26 m x 0.26 m Gross weigth 2.6 Net weigth 2.4 Vol. 0.0175	

general lighting that equally distributes all directions.

 $\left|\right\rangle$



ric Data

te System Value

40.10% CG 490.30 53.76

Optional : Extra cable length
Min. quantity, upcharge and extra lead time apply [EN]

ø 31 cm

200 cm

All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty

Vibia Lighting, S.L.U.

Office / Oficina Progrés 4-6. 08850 Gavà. Barcelona, Spain. International T +34 934 796 971 Spain / Portugal T +34 934 796 970

customer.service@vibia.com vibia.com